



ROLLSROLLER® SIGNATURE PLUS

ROLLSROLLER® SIGNATURE PLUS is our standard model and the perfect match for many. It has a wide range of options available.


THIS IS INCLUDED

ROLLSROLLER® Signature Plus Flatbed Applicator; Pneumatically controlled roller which is automatically adjusted for substrates up to 65 mm (2,56in)
LED illuminated table top; Smart electrical height adjustable table with memory settings; Flatbed worktable with a uniquely designed self-healing cutting mat; Roll holder on glide beam for pre-masking tape and laminate; Roll holder on bed end for printed or cut film; Stop static kit (cord and magnet) to remove static electricity; USB A & C ports; Casters (lockable); Owner's manual.

MODEL NAME	ROLLSROLLER® 300/170S Plus	ROLLSROLLER® 360/170S Plus	ROLLSROLLER® 360/212S Plus	ROLLSROLLER® 420/170S Plus	ROLLSROLLER® 420/212S Plus	ROLLSROLLER® 540/170S Plus	ROLLSROLLER® 540/212S Plus	ROLLSROLLER® 600/170S Plus	ROLLSROLLER® 600/212S Plus
Part no.	122-008	122-009	122-010	122-011	122-012	122-013	122-014	122-015	122-016
Model type	Signature Plus	Signature Plus	Signature Plus	Signature Plus	Signature Plus	Signature Plus	Signature Plus	Signature Plus	Signature Plus
Bed length	3040mm/ 9ft 11,7in	3640mm/ 11ft 11,3in	3640mm/ 11ft 11,3in	4240mm/ 13ft 10,9in	4240mm/ 13ft 10,9in	5440mm/ 13ft 10,2in	5440mm/ 13ft 10,2in	6040mm/ 19ft 9,8in	6040mm/ 19ft 9,8in
Bed width	1700mm/ 5ft 6,9in	1700mm/ 5ft 6,9in	2120mm/ 6ft 11,5in	1700mm/ 5ft 6,9in	2120mm/ 6ft 11,5in	1700mm/ 5ft 6,9in	2120mm/ 6ft 11,5in	1700mm/ 5ft 6,9in	2120mm/ 6ft 11,5in
Length of working area	2740mm/ 8ft 11,9in	3340mm/ 10ft 11,5in	3340mm/ 10ft 11,5in	3940mm/ 12ft 11,5in	3940mm/ 12ft 11,5in	5140mm/ 16ft 10,4in	5140mm/ 16ft 10,4in	5740mm/ 18ft 10in	5740mm/ 18ft 10in
Width of working area/roller width	1630mm/ 5ft 4,2in	1630mm/ 5ft 4,2in	2050mm/ 6ft 8,7in	1630mm/ 5ft 4,2in	2050mm/ 6ft 8,7in	1630mm/ 5ft 4,2in	2050mm/ 6ft 8,7in	1630mm/ 5ft 4,2in	2050mm/ 6ft 8,7in
Work height flatbed	800-1150mm/	800-1150mm/	800-1150mm/	800-1150mm/	800-1150mm/	800-1150mm/	800-1150mm/	800-1150mm/	800-1150mm/
Smart electrical height adjustment.	2ft 7,5in-3ft 9,3in	2ft 7,5in-3ft 9,3in	2ft 7,5in-3ft 9,3in	2ft 7,5in-3ft 9,3in	2ft 7,5in-3ft 9,3in	2ft 7,5in-3ft 9,3in	2ft 7,5in-3ft 9,3in	2ft 7,5in-3ft 9,3in	2ft 7,5in-3ft 9,3in
Max. thickness of substrate	65mm/ 2,56in	65mm/ 2,56in	65mm/ 2,56in	65mm/ 2,56in	65mm/ 2,56in	65mm/ 2,56in	65mm/ 2,56in	65mm/ 2,56in	65mm/ 2,56in
Bed surface	Glass + Cutting mat	Glass + Cutting mat	Glass + Cutting mat	Glass + Cutting mat	Glass + Cutting mat	Glass + Cutting mat	Glass + Cutting mat	Glass + Cutting mat	Glass + Cutting mat
Illuminated LED table- (dimnable)	yes	yes	yes	yes	yes	yes	yes	yes	yes
USB A & C port	yes	yes	yes	yes	yes	yes	yes	yes	yes
Roll holder on one short side	yes	yes	yes	yes	yes	yes	yes	yes	yes
Multi directional roll holder on glide beam	yes	yes	yes	yes	yes	yes	yes	yes	yes
Casters-movability	yes	yes	yes	yes	yes	yes	yes	yes	yes
Side trays for tool storage	yes	yes	yes	yes	yes	yes	yes	yes	yes
Powerful and ergonomic glide beam	yes	yes	yes	yes	yes	yes	yes	yes	yes
Stop static kit (cord and magnet)	yes	yes	yes	yes	yes	yes	yes	yes	yes

OUTPUT

Up to 2,05 meter (80in.) wide; Up to 5,74 meter (18ft 10in.) long.



60-80 m²/hr
(861 ft²/hr)

OPTIONS



Electrical Height-adjustable table



Additional Glide beam with roller



Antistatic system



VinylRemover



Motorized Glide beam



Media holder short side



Heat assisted roller



Extended roller adjustment



USB-C and A Charge port



Oil free Compressor



Air blow gun



EXC KeenCut EVO 3



Roll cradle 1 300 mm

UPGRADE YOUR ROLLSSROLLER®

PRODUCT NAME	PART_NO	PART.NO	PART NO.	PART NO.	PART.NO	PART.NO.	PART. NO	PART. NO	PART. NO
Additional glide beam with roller	121-003	121-003	121-004	121-003	121-004	121-003	121-004	121-003	121-004
Antistatic System	126-053	126-053	126-054	126-053	126-054	126-053	126-054	126-053	126-054
Air blow gun	126-055	126-055	126-055	126-055	126-055	126-055	126-055	126-055	126-055
EXC KeenCut EVO 3	71864	71864	71864	72520	71864	71864	72528	71864	71864
VinylRemover (incl. bracket)	71856	71856	71854	71854	71856	71854	71854	71854	71854
Additional roll holder on short side	126-029	126-029	126-030	126-029	126-030	126-029	126-030	126-029	126-030
Heat assisted roller 40°C-60°C	121-009	121-009	N/A	121-009	N/A	121-009		121-009	50118
Extended roller adjustment. Enables substrates up to 110 mm (4in.)	On request	On request	On request	On request	On request	On request	On request	On request	On request
Roll cradle 1 300	126-056	126-056	126-056	126-056	126-056	126-056	126-056	126-056	126-056
Oil free Compressor	50213	50213	50213	50213	50213	50213	50213	50213	50213
R-Drive, motorized glide beam	On request	On request	On request	On request	On request	On request	On request	On request	On request

WARRANTY

5 years limited warranty.
* On request contact your dealer

